

32Ch 1080P HD NVR with 2 SATA HDD

VCSDVR-XM2D32



Features

- 1) Support multiple high-definition network camera access, up to 5MP resolution;
- 2) Support VGA, HDMI 1080P full HD output simultaneously;
- 3) Support GB28181 & Onvif;
- 4) Supporting web, CMS, center platform management software MYEYE, provide SDK development;
- 5) Supports multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- 6) Support mobile monitor on iPhone, Android etc, Mobile APP: XMeye / GoodEye
- 7) Support multiple network services (DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP searches, Alarm Center, etc.);
- 8) Support multi-browser (IE, Chrome, Firefox, Safari)
- 9) Support more than 20 kinds of languages
- 10) Support P2P Cloud server www.xmeye.net / www.dvrcenter.net

Specifications

Model NO		VCSDVR-XM2D32
System	Main Processor	Huawei HIS chipset Hi3535
	Operating system	Embedded Linux
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
Display	Operation interface	16 bit real color GUI interface support mouse operation
	Display screen	(Take all network input as an example, others are depended on the selected channel mode) 1/4/8 /9/16/25/36screen
Video	Image encode	H.264(High Profile)
	Monitor quality	VGA:1080P,HDMI:1080P
	Playback quality	Max support 1080P NVR mode
	Encode capability	32CH 1080P Realtime (NVR mode)
	Decode capability	4CH 1080P Realtime (NVR mode)
	Multi-mode video input	NVR mode :32CH*1080P/16CH*1080P/8CH*1080P/32CH*960P/ 16CH*720P/16CH*4M/8CH*5M
	Motion detection	Each channel can set 192(16*12) detection area, can set multi-level of flexibility
Audio	Audio compression	G.711A
Record and playback	Record mode	Manual/Alarm/Motion detection/Timing
	Local playback	Max support 4CH 1080P playback synchronously
	Video search	Time,date,event,channel search
	Space occupation	Video:1080P 20~30G/day*channel, Audio:691.2MB/day*channel
Storage and back up	Video storage	Local HDD,Network
	Back up mode	Network backup,USB portable HDD,USB DVD-RW
	Video input	32CH 1080P
	Video output	1CH VGA,1CH HDMI

Interface	Audio input	1CH
	Audio output	1CH
	Alarm input	NO
	Alarm output	NO
	Network port	RJ45 1000M Ethernet port
	PTZ control	1 RS485,support multi kinds of PTZ Protocol
	USB port	2*USB2.0
	HDD port	2 SATA
	Wireless port	3G,WIFI(extension via USB port)
	Tour	Yes
other	Remote controller	Yes
	Power	12V/4A
	Dimension	325(Length) x 255(Width) x 60 (Height)
	Package	5cps/ctn